


Air Filter + Regulator + Lubricator

3 Units Air Combination

Series UFRL

◆ How to Order

UFRL – 02 N C D



Drain type

Nil	Semi-auto Drain
D	Auto drain
H	Manual drain

Filtration

Nil	5 μ m	C	40 μ m
-----	-------	---	--------

Thread

Nil	G	N	NPT
-----	---	---	-----

Port size


02	1/4	06	3/4
03	3/8	08	1
04	1/2		

Air Filter+Regulator+Lubricator

◆ Specifications

Model	UFRL-02	UFRL-03	UFRL-04	UFRL-06	UFRL-08
Port size	1/4	3/8	1/2	3/4	1
Fluid	Air				
Construction	Piston type regulator				
Body material	Aluminum die-cast				
Bowl material	Polycarbonate(standard)				
Filtration	5 μ m(standard), 40 μ m(option)				
Set pressure range	0.05~0.99 MPa				
Max. Inlet pressure(standard)	1.2 MPa				
Max. Flow rate	2080	2100	2600	7940	8200
Ambient and fluid temperature	-10℃~60℃(No freezing)				
Recommended lubricant	Turbin oil class 1(ISO VG32)				
Filter bowl capacity	105cc		210cc		
Lubricator bowl capacity	125cc		235cc		
Standard drain	Semi-automatic drain(below 0.05MPa)				
Net weight for standard	1800g		2650g		
Accessories	1 Gauge, 1 bracket, 4 screw, 1 plug				

Symbol



◆ Dimensions

